PAC-CLAD®


PETERSEN


Architectural Metal Roof, Wall and Perimeter/Roof Edge Systems




TABLE OF CONTENTS


3	PAC-CLAD PRODUCT RANGE	
4-7	PAC-CLAD STANDARD, SIMULATED AND ANODIZED FINISHES, AVAILABILITY	
8-9	WALL APPLICATIONS	
10-11	PRECISION SERIES HWP AND HIGHLINE WALL PANELS	
12	PRECISION SERIES BOX RIB WALL PANELS	
13	PRECISION SERIES TILES	
14-15	FLUSH AND REVEAL WALL PANELS	
16	BOARD AND BATTEN WALL PANELS	
17	MODULAR AL WALL PANEL SYSTEM	
18-19	EXPOSED FASTENER PANELS	
20-21	COMPOSITE PANEL SYSTEMS	
22-23	INSULATED METAL PANELS	
24	PERFORATED METAL	
25-27	WALL AND ROOF APPLICATIONS	
28-29	SNAP-CLAD	
30-31	TITE-LOC	
32-33	PAC-150	Available only from the Georgia, Arizona and Maryland facilities
34-35	PAC T-250	Available only from the Illinois and Texas facilities
36-37	SNAP-ON	
38-39	WALL AND ROOF APPLICATIONS	
40-41	SOFFIT PANELS	
42-43	PAC-SHIELD INSULATION	
44	PAC-CLAD HT UNDERLAYMENT	
45	GUTTER AND DOWNSPOUT SYSTEMS	
46	COLORGARD SNOW RETENTION SYSTEM, FLASHING AND TRIM	
47	FASCIA AND COPING SYSTEMS	
48	COLUMN COVERS, COIL AND FLAT SHEET	
49	BENDING GUIDELINES	
50-51	GENERAL CONSIDERATIONS	







































Cover Photo
Anne Carlsen Center, Jamestown, ND
Installing contractor: MG McGrath
Architect: JLG Architects
General contractor: Mortenson
Photo: alanblakely.com

Profiles: 7/8"Corrugated, 1/2" Corrugated
Colors: Bone White, Champagne
Custom Colors: Lemon Twist, Center Stage Green, Gulfstream, Purple

PAC-CLAD® PRODUCT RANGE

Petersen, a Carlisle company, manufactures PAC-CLAD architectural metal cladding products in multiple gauges of steel and aluminum. PAC-CLAD products include wall and roof panel systems and accessories, plus coil and flat sheet, all of which can be applied to nonresidential and residential structures. Founded in 1965, Petersen also operates production facilities in Illinois, Georgia, Texas, Maryland, Arizona and Washington. Petersen maintains a national network of field sales representatives to provide service to all 50 United States plus locations in Canada, Mexico and the Caribbean.

The range of PAC-CLAD products includes factory-produced wall and roof panel systems, soffit panels, flat sheet and coil, perforated aluminum, coping and fascia, column covers, snow retention systems, plus glass trim and storefront products. Available materials include PAC-CLAD prefinished 24 and 22 gauge steel; .032, .040, .050 and .063 gauge aluminum; 032 – .125 gauge mill finish aluminum; and anodized aluminum in .032 through .125 gauge.

WALL PANEL SYSTEMS

Wall systems include hidden-fastener and exposed-fastener panels, composite systems plus column covers. Aluminum panels, coil and flat sheet are available perforated in multiple combinations of hole sizes, shapes and spacing.

ROOF PANEL SYSTEMS

Standing seam roof panel profiles include mechanically seamed and snap-seam profiles. Multiple styles of soffit panels are offered in either solid or vented.

PERIMETER / EDGE PRODUCTS

Coping and fascia systems are available with matching flashing and trim, which can be factory-formed or field-formed from PAC-CLAD material. All Petersen perimeter systems are produced in 12' lengths for savings in material handling.

GUTTERS AND DOWNSPOUTS

PAC-TITE gutters, downspouts and scuppers improve water management performance while complementing a building's aesthetic qualities. Custom engineering promotes ease of installation and helps the drainage systems withstand harsh environments. The product line is Factory Mutual-approved and features ANSI/SPRI GT-1 compliance.

PAC-CLAD COLORS

PAC-CLAD is a versatile and durable coating of 70% polyvinylidene fluoride (PVDF) made with Kynar 500 resin that is applied to Galvalume steel or prime quality aluminum. A 35-year finish warranty is included with Petersen's standard colors. Custom colors are available. Most colors meet LEED requirements and are rated by the Cool Roof Rating Council. Galvalume Plus is available.

WARRANTIES

Petersen offers a 35-year finish warranty against fading and chipping, plus a coastal finish warranty against saltwater exposure for PAC-CLAD aluminum only. An optional weathertightness warranty is offered. Technical assistance and service are available from a nationwide network of architectural representatives who can assist with material selection, finish specification, installation and budgeting.



Bandwidth Inc. Headquarters, Raleigh, NC
Installing contractor: Baker Roofing Company
Architect: Gensler
Distributor: ABC Supply
General contractor: Brasfield & Gorrie LLC
Photo: hortonphotoinc.com
Profile: Tite-Loc Plus
Color: Graphite

PAC-CLAD® SINGLE SKIN STANDARD COLOR CHART

FINISH WARRANTY

Life expectancy is 35 years-plus on 70% PVDF-finished materials. A 35-year, non-prorated finish warranty covering color fade, chalking and film integrity is available at no extra charge. Warranty for Weathered Steel and Weathered Copper does not cover fade. Warranty for Cardinal Red and Award Blue is 10 years for fade and chalking, and 20 years for adhesion.

SINGLE SKIN PREMIUM COLORS

Petersen's premium colors include several metallic finishes, plus two-coat finish Weathered Steel. These colors are ideal for all building envelope applications. A PAC-CLAD 35-year, non-prorated finish warranty applies.

TRIM

PAC-CLAD products are available in prime quality aluminum (.032 - .063), 24 and 22 gauge Galvalume steel, finished with a 70% PVDF finish on the top side, with a washcoat on the bottom. Other metals available include mill finish aluminum, stainless steel, Galvalume Plus and anodized aluminum.

A strippable vinyl film can be applied to coil, flat sheet or fabricated parts to protect painted surfaces. Vinyl masking is recommended where extra handling is expected. NOTE: Vinyl film must be removed immediately after installation.

COMMITMENT TO SUSTAINABILITY

PAC-CLAD products provide unmatched aesthetics and performance, plus an element of sustainability. Where possible, Petersen's PAC-CLAD products include a high percentage of recycled material, which lowers their environmental footprint. Additionally, Petersen products are 100% recyclable which may reduce the stream of solid waste to landfills.

Petersen also offers the industry's widest range of standard colors, most of which feature outstanding SRI (Solar Reflectance Index) values for improved cooling and energy savings performance. Petersen offers multiple finishes that are rated by the Cool Roof Rating Council. In addition, many PAC-CLAD finishes have an SRI of 29 or higher for steep slope roofs, to allow a building to qualify for credits in the U.S. Green Building Council's Leadership in Energy and Environmental Design (LEED) building rating system.

NOTE: Colors shown on this page are not exact representations of actual PAC-CLAD colors. Ask a Petersen representative for a color-chip chart or painted metal samples before making final color selection.

SINGLE SKIN STANDARD COLORS

Bone White*
Stone White*
Almond*
Sandstone*
Sierra Tan*
Buckskin*
Medium Bronze*
Aged Bronze*
Dark Bronze*
Burnished Slate*
Granite*
Antique Bronze*
Classic Bronze*
Midnight Bronze
Mansard Brown*
Cityscape*
Slate Gray*
Musket Gray*
Charcoal*
Graphite*
Black (fka Black Aluminum)
Iron Ore*
Inkwell
Onyx (fka Matte Black)
Traditional Black
Terra Cotta*
Colonial Red*
Burgundy
Cardinal Red*
Military Blue*
Pacific Blue* (fka Slate Blue)
Interstate Blue
Berkshire Blue
Award Blue
Hemlock Green*
Forest Green
Patina Green*
Hartford Green
Galvalume Plus

SINGLE SKIN PREMIUM

Anodic Clear*
Silversmith*
Silver*
Champagne*
Weathered Zinc*
Copper Penny*
Weathered Steel

* Denotes PAC-CLAD Cool Color

SHERWIN-WILLIAMS Coil Coatings

Petersen has been a proud partner with Sherwin-Williams Coil Coatings since 1972

PAC-CLAD® PERFORMANCE AND AVAILABILITY

STANDARD COLORS	REFLECTIVITY	EMISSIVITY	3 YEAR EXPOSURE	SRI	STEEL		ALUMINUM				20-IN. COIL	
					24 GA.	22 GA.	.032	.040	.050	.063	24 GA.	.032
AWARD BLUE †	0.25	0.86	0.23	24	✓		✓					
BLACK (FKA BLACK ALUMINUM)	0.05	0.90	0.04	0	✓	✓	✓	✓	✓	✓	✓	✓
BONE WHITE	0.70	0.86	0.69	85	✓	✓	✓	✓	✓	✓	✓	✓
BURNISHED SLATE	0.32	0.86	0.31	33	✓						✓	
CARDINAL RED †	0.44	0.86	0.44	49	✓		✓				✓	✓
CHARCOAL	0.30	0.87	0.30	31	✓		✓	✓	✓		✓	✓
CITYSCAPE	0.05	0.87	0.50	57	✓	✓	✓	✓	✓		✓	✓
CLASSIC BRONZE * NEW	0.27	0.87	N/A	27	✓						✓	
COLONIAL RED	0.34	0.87	0.31	36	✓		✓	✓	✓		✓	✓
DARK BRONZE	0.27	0.86	0.29	26	✓	✓	✓	✓	✓	✓	✓	✓
FOREST GREEN	0.10	0.88	0.10	5	✓		✓	✓			✓	✓
GRANITE *	0.32	0.86	0.33	33	✓	✓	✓	✓	✓			✓
GRAPHITE	0.25	0.86	0.28	24	✓						✓	
HEMLOCK GREEN	0.31	0.87	0.30	32	✓		✓				✓	
INKWELL * NEW	0.27	0.86	N/A	26	✓						✓	
INTERSTATE BLUE	0.16	0.87	0.15	12	✓		✓		✓		✓	✓
IRON ORE NEW	0.27	0.87	N/A	27	✓		✓	✓	✓		✓	✓
MANSARD BROWN	0.31	0.87	0.31	32	✓		✓	✓	✓		✓	✓
MEDIUM BRONZE	0.30	0.88	0.29	31	✓	✓	✓	✓	✓	✓	✓	✓
MIDNIGHT BRONZE	0.06	0.90	0.06	1	✓			✓			✓	
MUSKET GRAY	0.32	0.87	0.31	33	✓	✓	✓		✓		✓	✓
PACIFIC BLUE (fka SLATE BLUE)	0.28	0.87	0.27	28	✓		✓				✓	✓
SANDSTONE	0.48	0.87	0.48	55	✓	✓	✓	✓	✓	✓		
SIERRA TAN	0.38	0.85	0.31	40	✓	✓	✓	✓	✓		✓	✓
SLATE GRAY	0.41	0.87	0.37	45	✓	✓	✓	✓	✓		✓	✓
STONE WHITE	0.69	0.86	0.67	84	✓	✓	✓	✓	✓	✓		
TERRA COTTA	0.35	0.87	0.33	37	✓		✓		✓		✓	✓
TRADITIONAL BLACK * NEW	0.28	0.87	N/A	28	✓		✓				✓	✓
EXTENDED LEAD TIME												
AGED BRONZE	0.29	0.87	0.27	29	✓						✓	
ALMOND	0.63	0.85	0.55	75	✓	✓	✓	✓	✓			
ANTIQUE BRONZE NEW	0.28	0.86	N/A	27	✓		✓	✓			✓	✓
BERKSHIRE BLUE *	0.29	0.86	0.27	29	✓							
BUCKSKIN NEW	0.37	0.86	N/A	39	✓						✓	✓
BURGUNDY	0.24	0.86	0.13	22	✓						✓	
HARTFORD GREEN	0.08	0.88	0.08	3	✓			✓			✓	
MILITARY BLUE	0.31	0.87	0.30	32	✓		✓				✓	✓
ONYX (fka MATTE BLACK STEEL)	0.26	0.85	0.25	24	✓	✓					✓	
PATINA GREEN	0.33	0.86	0.32	34	✓							
WEATHERED STEEL 👑	0.26	0.86	N/A	25	✓							
PREMIUM COLORS												
ANODIC CLEAR 👑	0.53	0.81	0.31	60				✓				
CHAMPAGNE 👑	0.40	0.78	0.49	40	✓		✓	✓	✓			✓
COPPER PENNY 👑	0.50	0.86	0.52	57	✓		✓	✓			✓	✓
SILVER 👑	0.47	0.82	0.46	52	✓	✓	✓	✓	✓		✓	✓
SILVERSMITH 👑	0.54	0.81	0.32	61				✓				
WEATHERED ZINC 👑	0.24	0.83	0.46	21	✓		✓		✓		✓	✓
CLEAR-COAT ACRYLIC FINISH (NON-PVDF)												
GALVALUME PLUS	0.68	0.14	0.55	57	✓	✓					✓	

PAC-CLAD Premium finishes are available from stock at a moderate extra cost. PAC-CLAD Copper Penny is a Non-Weathering finish. Solar Reflectance Index calculated according to ASTM E-1980. Reflectivity and solar reflectance index (SRI) values are provided by Sherwin-Williams®.

TECHNICAL DATA FOR 70% PVDF COATING:

- South Florida Exposure: Color (ASTM D 2244) - No more than 5ΔE Hunter units at 20 years; Chalk (ASTM D 4214) – Rating no less than 8 at 20 years; Film integrity – 20 years.
- Accelerated Weathering (ASTM D 4587, ASTM G 154): 5000 Hours; Chalk, per ASTM D 4214, rating of 6 or better; Color, per ASTM D 2244, < 5ΔE (Hunter Units) color change.
- Chemical/Acid Pollution Resistance (ASTM D 1308): Pass
- T-Bend (ASTM D 4145): 1T – 3T with no loss of adhesion
- Humidity Resistance (ASTM D 2247): Galvalume or HDG, 100% RH, 2000 hours – No field blisters; Aluminum, 100% RH, 3000 hours – No field blisters
- Salt Spray Resistance (ASTM B 117): Aluminum: 3000 hours, creep from scribe no more than 1/16" (2mm), no field blisters. Galvalume or HDG:2000 hours, creep from scribe no more than 1/8" (4mm), no field blisters
- Pencil hardness (ASTM D 3363): HB – 2H
- Specular Gloss (ASTM D 523) @ 60 degrees: Typical – 20 – 35
- Abrasion Resistance (ASTM D 968): 80 Liters/Mil +/- 5 Liters
- Cross Hatch Adhesion (ASTM D 3359): No loss of adhesion
- Reverse Impact (ASTM D 2794): Galvalume or HDG, 2x metal thickness inch-pounds, no loss of adhesion; Aluminum, 1.5x metal thickness inch-pounds, no loss of adhesion
- Flame Test (ASTM E 84): Class A Coating

* Low Gloss/Low Sheen, 70% PVDF finish † 10-year finish warranty 👑 Premium Colors

TIMBER SERIES WOOD GRAIN FINISHES





Brown Timber



Copper Timber



Gray Timber



Tan Timber



White Timber

When the performance of metal is required but the look of wood is desired, PAC-CLAD Timber Series wood grain finishes from Petersen are ready to dazzle. Timber Series wood grain patterns will convince the casual observer that metal is actually wood. A lineup of five wood grain patterns ensures creative design and flexibility and can deliver a finishing touch to any project.

Timber Series PVDF wood grain finishes combine the beauty of wood with the durability of metal. The patterns are nearly indistinguishable from actual wood, and they provide architects and designers with creative flexibility on highly functional surfaces. Wood grain finishes are available on all PAC-CLAD wall single skin panels. Consult PAC-CLAD representative to discuss warranty, lead time and related issues.

▲ Printed colors are not exact representations of actual PAC-CLAD Wood Grain Finishes. Please ask a PAC rep for color samples before making a final selection.

Photo above: Waterford Bay Apartments, St. Paul
Installing contractor: MG McGrath
Architect: BKV Group
General contractor: Benson-Orth
Photo: alanblakely.com
Profiles: Box Rib 1, Flush panel, Reveal panel
Colors: Weathered Zinc, Onyx, Custom Rustic Amber, Custom Classic II Bronze

PRODUCT FEATURES

- Steel: 24 gauge
- Aluminum: .032

SIMULATED FINISH TESTING

- ASTM D 3359
- ASTM D 4145
- ASTM D 3363
- ASTM D 2794
- ASTM D 968
- ASTM D 523
- ASTM B 117
- ASTM D 2247
- ASTM D 3361

Note: Additional simulated Wood Grain and Ore finishes, as well as custom simulated finishes are available; consult rep for details.

ANODIZED ALUMINUM


Holland America Cruise Line Headquarters, Seattle, WA


Clear Anodized


Dark Bronze Anodized


Black Anodized

ANODIZED ALUMINUM

Anodized aluminum allows designers to inject creativity into any project. Petersen's collection of anodized finishes includes the essentials: Clear, Dark Bronze and Black. For whatever signature look is desired, anodized aluminum can deliver beauty, long-lasting performance, light weight and corrosion resistance.

The anodized finishes are highly resistant to ultraviolet light, and reflect years of research and investment in control of uniformity and appearance. The investment has resulted in the most consistent anodized finishes in the market.

Note: Finish warranty available on some anodized aluminum.

⚠ Printed colors are not exact representations of actual PAC-CLAD Finishes. Please ask a PAC rep for color samples before making a final selection.


ANODIZED COLORS	.032	.040	.050	.060	.080	.125
PAC CLEAR ANODIZED*	✔	✔	✔	✔	✔	✔
PAC DARK BRONZE ANODIZED*	✔	✔	✔	✔	✔	
PAC BLACK ANODIZED*		✔	✔	✔	✔	

*Stocked


Note: More finishes are available but with longer lead time and subject to minimum quantities; consult rep for details.

LORIN | Anodized metal is offered proudly through a partnership with Lorin Industries.

PAC-CLAD® WALL PANEL APPLICATIONS



Children's Museum & Theatre of Maine, Portland, ME
Installing contractor: Industrial Roofing and Siding
Architect: Bruner/Cott Architects
Distributor: North Bridge Building Products
General contractor: Zachau Construction
Owner: The Children's Museum & Theatre of Maine
Photo: hortonphotoinc.com
Profile: Precision Series Tiles (TS)
Colors: Stone White, Granite, Cityscape, Berkshire Blue



The Charles, Atlanta
Installing contractor: Pierre Construction Group
Architect: Lord Aeck Sargent
Distributor: Commercial Roofing Specialties
General contractor: Brasfield and Gorrie
Owner: The Charles Master and Residential Condo Associations Inc.
Photo: hortonphotoinc.com
Profile: 7.2 panel perforated
Color: Weathered Zinc



John S. McCain III Elementary School, Buckeye, AZ
Installing contractor: Global Roofing Group
Architect: Orcutt | Winslow
General contractor: Chasse Building Team
Owner: Buckeye Elementary School District #33
Photo: Brian Adams
Profiles: 7.2 panel solid and perforated, Snap-Clad, Flush panel, M-36 solid and perforated
Colors: Award Blue, Cityscape, Stone White



West Point Junior High, West Point, UT
Installing contractor: LCG Facades
Architect: VCBO Architecture
General contractor: Hogan Construction
Photo: alanblakely.com
Profiles: Highline C1, Highline S2
Colors: Cityscape, Charcoal

PRECISION SERIES HWP AND HIGHLINE WALL PANELS



PRODUCT FEATURES

- No-clip panel, or clip installation for expansion/contraction
- Multiple rib patterns provide a variety of looks and design options
- Panel depths of ⅞" or 1-⅜"
- Cost-effective installation
- Horizontal or vertical installation
- Micro-seam corners available
- Panel lengths:
  30' maximum for steel;
  22' maximum for aluminum on the thru-fastened leg; longer lengths available on clip panels

MATERIAL

- 24 gauge steel
- 22 gauge steel
- .032 aluminum
- .040 aluminum
- .050 aluminum
- Galvalume Plus available

TESTS

- ASTM E330
- ASTM E331
- ASTM E283
- ASTM 1592
- AAMA 501.1-05-B1, B2, C2, S1

FLORIDA BUILDING PRODUCT APPROVALS

Please refer to pac-clad.com or your local factory for specific product approval numbers for Precision Series panels.



HWP


WITH OR WITHOUT CLIP

MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

12" or 16" Wide
7/8" High





HIGHLINE B1

WITH OR WITHOUT CLIP

MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

11.356" Wide
1-3/8" High





HIGHLINE B2


WITH OR WITHOUT CLIP

MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

15.356" Wide
1-3/8" High



NOTE: Oil canning is not a cause for rejection.

Precision Series architectural wall panels provide design flexibility by combining bold visual effects with easy, cost-effective installation. Multiple profiles are available with a variety of rib patterns. Options for each profile include a no-clip panel, or a clip-fastened panel to accommodate expansion and contraction.

The original Precision Series HWP profile features a ⅞" depth, while the Precision Series Highline profiles are 1-⅜" deep, and can be intermixed to add visual intensity to a building's exterior. Precision Series wall panels can be installed horizontally or vertically.

Consult Petersen rep for maximum length; minimum panel length is 4'. Additionally, these wall panels can be specified as perforated in aluminum only for use in equipment screen applications, over graphics or for architectural flair.



HIGHLINE C1

WITH OR WITHOUT CLIP

MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

11.356" Wide
1-3/8" High





HIGHLINE C2


WITH OR WITHOUT CLIP

MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

15.356" Wide
1-3/8" High





HIGHLINE M1

WITH OR WITHOUT CLIP

MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

12.043" Wide
1-3/8" High





HIGHLINE S1

WITH OR WITHOUT CLIP

Note: Minimum panel length is 5'

MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

11.356" Wide
1-3/8" High





HIGHLINE S2

WITH OR WITHOUT CLIP


Note: Minimum panel length is 5'

MATERIALS

.050 aluminum
22 gauge steel

SPECS

15.356" Wide
1-3/8" High



NOTE: Oil canning is not a cause for rejection.

Highline panels should be installed in single-piece runs, either horizontally (male side down) or vertically. For aluminum panels more than 22' or steel panels more than 30' the clip version should be utilized. Contact PAC rep for longer length options. Box Rib panels are NOT designed to be field-lapped over one another.

JOINT DETAILS

CLIP



FASTENER FLANGE



Note: Line drawings on these two pages are not to scale.

PRECISION SERIES BOX RIB WALL PANELS

Precision Series Box Rib architectural wall panels provide design flexibility by combining bold visual effects with easy, cost-effective installation. Multiple profiles are available with a variety of rib patterns. Each profile is offered in a no-clip panel, or a clip-fastened panel to accommodate expansion and contraction.

The Box Rib profiles are 1-3/8" deep and a nominal 12" wide. All precision Series profiles, including Box Rib, Highline and HWP, can be intermixed to add visual intensity to a building's exterior. Precision Series wall panels can be installed horizontally or vertically. Consult Petersen rep for maximum length; minimum panel length is 4'.

Additionally, Precision Series wall panels can be specified as perforated but only in aluminum for use in equipment screen applications, over graphics or for architectural flair.

PRODUCT FEATURES

- No-clip panel, or clip installation for expansion/contraction
- Panel depth 1-3/8" nominal
- Panel width of 12" nominal
- Cost-effective installation
- Horizontal or vertical orientation
- Micro-seam corners available
- Panel length: 30' maximum for steel
- Panel length: 22' maximum for aluminum on the thru-fastened leg (no clip), longer lengths available on clip panels

TESTING

- ASTM E330
- ASTM E283
- ASTM E331
- AAMA 501.1-05
- ASTM 1592

MATERIALS

- 24 gauge steel
- 22 gauge steel
- .032 aluminum
- .040 aluminum
- .050 aluminum
- Galvalume Plus available



BOX RIB 1

WITH OR WITHOUT CLIP


MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

12" Wide
1-3/8" High

Note: Minimum panel length is 4'





BOX RIB 3

WITH OR WITHOUT CLIP

MATERIALS


.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

12" Wide
1-3/8" High

Note: Minimum panel length is 4'





BOX RIB 2

WITH OR WITHOUT CLIP

MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

12" Wide
1-3/8" High

Note: Minimum panel length is 4'



NOTE: Line drawings on this page are not to scale.
NOTE: Oil canning is not a cause for rejection.



BOX RIB 4

WITH OR WITHOUT CLIP


MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel

SPECS

12" Wide
1-3/8" High

Note: Minimum panel length is 4'



Box Rib panels should be installed in single-piece runs, either horizontally (male side down) or vertically. For aluminum panels more than 22' or steel panels more than 30' the clip version should be utilized. Contact PAC rep for longer length options. Box Rib panels are NOT designed to be field-lapped over one another.

JOINT DETAILS

CLIP



FASTENER FLANGE



PRECISION SERIES TILES

The Precision Series Tiles collection from Petersen includes three metal tile profiles that offer designers, specifiers and installers an alternative to roll-formed panel-style cladding. The stamped tiles can be applied to roof or wall installations, and are offered in three styles including Cupped, Flat and Diamond. Designed to enhance architectural design, the tiles add dimension to the exterior of any structure. The tiles can be applied to either commercial or residential environments, and are covered by the PAC-CLAD 35-year finish warranty.

The interlocking tiles are formed using progressive tooling to create a uniform and cost-effective cladding solution. This system installs directly over plywood or elevated channels using concealed fasteners. No sealant is required for the tiles' breathable joints. Thermal gain and movement is not an issue, as the small size of each tile means movement will be minimal. Only basic sheet metal tools are required to work with these products. Minimum slope of 3:12 for roof applications.

PRODUCT FEATURES

MATERIAL

- 24 gauge steel
- .032 aluminum
- .032 anodized
- Zalmag® coated steel (26 gauge) (Sold only in Florida and Texas)

ASTM TESTS

- ASTM E283
- ASTM E330
- ASTM E331


UL CLASSIFICATION

- UL 580-1897

AAMA TESTS

- AAMA 501.1

CUPPED TILE



FLAT TILE



DIAMOND TILE



CUPPED TILE

The cupped tile catches light at multiple angles that creates a multi-shade effect as viewing perspective changes. In roof applications, installers can safely walk on the cupped tiles during installation.

- Nominal: 15" x 9-5/8"
- Exposed: 14-1/2" x 8-5/16" +/- 1/16"

FLAT TILE


The flat tile has the flexibility to integrate with both modern and traditional designs.

- Nominal: 15" x 9-5/8"
- Exposed: 14-1/2" x 8-5/16" +/- 1/16"

DIAMOND TILE

Diamond tiles can be installed horizontally, or on an angle to achieve a diamond or clapboard pattern.

- Nominal: 8-5/16" x 9-3/4"
- Exposed: 7-1/4" x 8-5/16" +/-1/16"



Minneapolis-St. Paul Airport Loading Dock, Minneapolis
Contractor: Progressive Building Systems
Architect: Miller Dunwiddie Architecture
General contractor: Sheehy Construction
Photo: bergphoto.com
Profile: Precision Series Tiles (cupped)
Colors: Patina Green, Hemlock Green, Arcadia Green, Custom Aged Copper

FLUSH AND REVEAL WALL PANELS

Flush and Reveal panels are designed for wall, fascia and soffit applications where a flat appearance is desired. A rounded interlock leg and concealed fastening system improves the flush appearance while providing additional strength. Panels are factory-formed to length to minimize field cutting. Maximum panel length is 25′ and minimum panel length is 4′.

Flush panels are available in on-center dimensions designed to complement Petersen's roofing panel product line. Flush and Reveal joint configurations are available.

PENCIL RIBS

The Flush and Reveal panels are available with optional pencil ribs. Pencil ribs are recommended for longer panel lengths. One or two ribs are available.

INSTALLATION

Flush and Reveal panels shall be installed over a solid substrate with appropriate ice and water shield, or in limited applications over framing sections. When used in a windscreen application, panels must be fastened (stitched) through side joints. Consult a local architect/engineer for requirements of local codes and conditions.

OPTIONAL CLIP

An optional patented concealed fastening clip is available on the 12″ panel only to raise a panel assembly's wind resistance performance level. The optional clip has been designed and tested to resist disengagement during high-wind events.

TRIM

All flashing and trim shall be fabricated by Petersen or qualified fabricator. Flashing shall be PAC-CLAD aluminum or PAC-CLAD steel. A 35-year non-prorated finish warranty can be supplied covering finish performance. Minimum bending radius is 2T. Vinyl masking is recommended on all fabrication applications where extra handling is expected. NOTE: The strippable vinyl film must be removed immediately after installation.

HORIZONTAL APPLICATIONS

When installing Flush and Reveal panels horizontally, install first panel at top of wall and proceed to bottom.

OIL CANNING

Jobsite factors such as temperature variation, unlevel substrate and/or improper installation may promote oil canning. Oil canning does not affect panel finish or structural integrity and therefore is not cause for rejection.


NOTE: Oil canning is not a cause for rejection. An oil canning agreement is required when ordering lengths over 8′-0″ (24 ga. steel or .032″ aluminum) and over 20′-0″ (22 ga. steel or .040″ aluminum).



Lone Star College East Aldine Satellite Center, Houston
Contractor: PRC Roofing and Sheet Metal
Architect: Texas IBI Group
GC: Bartlett Cocke
Photo: alanblakely.com
Profiles: Highline S1, Flush panel
Colors: Copper Penny, Cardinal Red



Kirkwood Performing Arts Center, Kirkwood, MO
Installing contractor: David J. Hyde & Associates
Architect: Jacobs
General contractor: BSI Constructors
Owner: City of Kirkwood
Photo: alanblakely.com
Profiles: Flush panel, Reveal panel
Colors: Graphite, Musket Gray, Slate Gray




FLUSH PANEL


MATERIALS


.032 aluminum
.040 aluminum*
24 gauge steel
22 gauge steel*


SPECS

7", 11", or 12" O.C.
1" High










REVEAL PANEL


MATERIALS


.032 aluminum
.040 aluminum*
24 gauge steel
22 gauge steel*

SPECS

7", 11", or 12" O.C.
1" High







NOTE: Oil canning is not a cause for rejection.

- 12" O.C. has reduced fastener flange
- Clip not shown in drawings above
- A complete specification is available online at pac-clad.com.

PRODUCT FEATURES

- Available with up to two pencil ribs
- Rounded interlock leg provides improved flush fit
- Optional clips available for added wind resistance requirements (clips can be used on all widths but were tested only on the 12-in. panel)
- 35-year non-prorated finish warranty
- Panel lengths from 4' to 25'

MATERIAL

- 24 gauge steel
- 22 gauge steel
- .032 aluminum
- .040 aluminum
- Galvalume Plus available

ASTM TESTS - FLUSH

- ASTM E330 (only the 12" panel was tested)
- ASTM 1592
- ASTM E283
- ASTM E331
- AAMA 501.1-05

FLORIDA BUILDING PRODUCT APPROVALS

Please refer to pac-clad.com or your local factory for specific product approval numbers for Flush panels.

*Limited color availability.

BOARD AND BATTEN WALL PANELS

The Board and Batten panel system provides a timeless design aesthetic for commercial and residential wall applications. It uses a concealed fastener system to maintain clean lines and a rhythmic pattern of alternating wide vertical boards and narrower elevated battens. The ¾" batten depth and 2" width create dimensional interest while keeping trim offsets to a minimum. Board and Batten panels blend smoothly into various architectural styles. Whether creating a cozy and inviting facade or a bold and striking statement, Board and Batten exterior wall panels remain a versatile tool for architectural creativity.

PRODUCT FEATURES

- Installs with concealed mechanical fasteners through pre-punched holes
- Vertical wall applications only
- Widths - 12", 16"
- Batten is 2" wide and ¾" deep on all panel widths
- Maximum length for steel is 30 feet
- Maximum length for aluminum is 22 feet

TESTING

- ASTM E283
- ASTM E331
- AAMA 501.1
- ASTM E330
- TAS 202
- TAS 203



BOARD AND BATTEN

MATERIALS


.032 aluminum

24 gauge steel

SPECS

12" or 16" Wide

3/4" High



NOTE: Oil canning is not a cause for rejection.










MODULAR AL WALL PANEL SYSTEM

The PAC-CLAD Modular AL panel system from Petersen empowers designers to create unique cassette-style metal cladding surfaces using panels of various sizes and depths and in multiple colors. Panel dimensions can be standardized, or designers can define panel dimensions and depths to create truly unique, flexible and eye-catching patterns. Vertical or horizontal panels can be combined in the same layout. Panels can be finished in any combination of the standard PAC-CLAD colors, or custom colors. Panels can be perforated, including in specific patterns that spell words or form logos. Installation of Modular AL panels can be performed on a variety of substrates including plywood, insulation, purlins or any combination of these.





MODULAR AL

MATERIALS	MAX DIMENSIONS
.050 aluminum	16-in. by 120-in.
.063 aluminum	16-in. by 120-in.
.080 aluminum	16-in. by 120-in.

SPECS

Standard Sizes:	16" x 72", 16" x 120"
Depth range:	1 3/8-in. to 3-in.
Joint range:	1/2-in. to 1-in.
Custom sizes:	Consult factory rep




Photo above:
La Crosse Fire Department Station No. 2, La Crosse, WI
Installing contractor: Bluewaters Companies
Architect: Wendel
Distributor: ABC Supply
General contractor: Market & Johnson
Owner: City of La Crosse, WI
Photo: alanblakely.com
Profile: Modular AL
Colors: Granite, Sandstone, Champagne


PRODUCT FEATURES


- Flat or tapered
- No sealants
- Concealed fasteners
- Easy installation
- Can be perforated
- Custom sizes
- 35-year finish warranty
- Made of 100% recycled aluminum
- Full fabrication package on all projects
- Weep holes for pressure and moisture venting
- Mix and match panel depths and sizes
- Stacked and running bond designs available

TESTING

- E283
- E331
- E330
- AAMA 508


DESIGN CONFIGURATIONS


Running Bond


Stacked


Mosaic

Depth Range
1 3/8-in. to 3-in.



Scan to view AR model. Place it in your space, walk around it.



EXPOSED FASTENER PANELS



Petersen offers a complete line of exposed fastener panels, allowing for creative design flexibility in a cost-effective yet architecturally attractive metal panel. The versatile 7.2 panel, R-36 and ⅞" Corrugated panels can be specified for a wide range of building envelope applications including roofs, walls and linear panels. The M-36, M-42 and ½" Corrugated panels are suitable for wall and equipment screen projects.

TRIM

All flashing and trim shall be fabricated by Petersen or qualified fabricator. Flashing shall be PAC-CLAD aluminum (.032 - .063 gauge as specified) or PAC-CLAD steel (24 gauge or 22 gauge as specified). A 35-year non-prorated finish warranty can be supplied covering finish performance. Minimum bending radius is 2T; consult rep for details.

Vinyl masking is recommended on all fabrication applications where extra handling is expected. NOTE: The strippable vinyl film must be removed immediately after installation.

PRODUCT FEATURES

- 35-year non-prorated finish warranty
- Matching screws and rivets
- Closure strips available
- Precut short lengths (5'-0" minimum) (3'-0" on the M-42)
- Max panel length varies by facility; Consult rep for details

MATERIAL

- 24 gauge steel
- 22 gauge steel
- .032 aluminum
- .040 aluminum
- .050 aluminum
- Galvalume Plus available


FLORIDA BUILDING PRODUCT APPROVALS

Please refer to pac-clad.com or your local factory for specific product approval numbers for exposed fastener panels.

Photo above:
Hurricane Harbor, Six Flags Over Georgia, Austell, GA
Installing contractor: R.E. Primm & Co.
Architect: Hill, Foley, Rossi and Associates
General contractor: McMichael's Construction Co.
Distributor: CRS
Photo: hortonphotoinc.com
Profiles: M-36 and Snap-Clad panels
Colors: Patina Green, Terra Cotta and Military Blue




R-36 PANEL




MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel




M-42 PANEL*




Note: Made only in Tyler, Texas facility

M-36 PANEL*




MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel




7.2 PANEL




MATERIALS

.032 aluminum
.040 aluminum
.050 aluminum
24 gauge steel
22 gauge steel






7/8" CORRUGATED



1/2" CORRUGATED



*Note: The M-36 and M-42 panels are not intended for use in the construction of metal buildings or structural roof applications. Please consult with Petersen regarding the application of this panel.

A complete specification is available online at pac-clad.com.

Photo at left:
Hurricane Dockside Grill, Hagerstown, MD
Contractor: Heidler Roofing
Photo: David Fonda
Profile: R-36 panel
Color: Cardinal Red

PAC-3000 COMPOSITE PANEL SYSTEMS



White Orthodontics, Saginaw, MI
Contractor: Graham Construction
Architect: Arch 1 ltd
Distributor: Oakland Metal Sales
Photo: alanblakely.com
Profiles: PAC-3000 RS
Colors: Limestone, Deep Black

Petersen offers another dimension in design flexibility with its series of composite wall panels. PAC's panel systems provide unmatched performance and stunning visual effects for any commercial or retail application.

The PAC-3000 CS panels are comprised of an .020 face and back skin thermobonded to a polyethylene or fire-retardant core. Panels are formed by a rout-and-return process utilizing computer-controlled routing equipment. This state-of-the-art fabrication ensures tight tolerances and accurate panel dimensions. Staggered angle clips mounted to the panel allow for each panel to be installed and adjusted individually.

The PAC-3000 RS is a rain-screen system that eliminates the use of caulk, utilizing clean reveals for an architecturally pleasing system. The system is constructed with metal composite material (MCM), available in a wide range of finishes and colors to complement any design scheme. Extrusions are fixed to the perimeter of the panel and nest into the extruded track which is attached to the substrate. The result is a free-floating panel installation since the panel is not fastened to the substrate.

COLORS

The PAC-CLAD colors on pages 4-7 do not apply to composite panels. Consult Petersen rep for color options.

PRODUCT FEATURES

- Available in a wide variety of non-PAC-CLAD colors and finishes
- Precise fabrication to meet exacting tolerances
- Rout-and-return fabrication
- Welded corners available

MATERIAL

- 3mm, 4mm, 6mm – Composite
- .063 - .125 Mill Finish Aluminum
- Anodized aluminum
- Zinc
- Stainless steel

TESTS

- ASTM E283*, ASTM E330*, ASTM E331*


*Composite material only




PAC-3000 CS



PAC-3000 RS






PAC-4000 COMPOSITE PANEL SYSTEMS


PAC-4000 is a 4mm composite panel made by bonding a prefinished aluminum skin to a substrate of thermoset phenolic resin. A second aluminum skin is added as a backer and provides thermal stability and panel balance. Panels are furnished with a strippable film on the painted surfaces to protect the finish during shipment and installation.

PAC-4000 is an exterior cladding designed for walls, canopies, fascia and accents on all building types including hospitals, office buildings, retail, educational facilities and many more.



PAC-4000 REVEAL (RV)

REVEAL PROFILE / BATTEN PROFILE





PAC-4000 DEEP REVEAL (DRV)

STANDARD JOINT / VARIABLE JOINT

COLORS: The PAC-CLAD colors on pages 4-7 do not apply to composite panels. Consult Petersen rep for color options.

ATTACHMENT SYSTEMS

SYSTEM	SYSTEM TYPE	SYSTEM PERFORMANCE	CLADDING TYPE	TYPE OF JOINT	LEAD TIME
PAC-4000 REVEAL (RV) Fabricated Look in a Field-Assembled System 	Field-Assembled	ASTM E283 ASTM E330 ASTM E331 NFPA 285 ICC-ESR-1015 FL14436.3	Barrier Wall	Low Profile Batten and Reveal (½") Moldings	15 Business Days
PAC-4000 DEEP REVEAL (DRV) Hybrid Approach to System Installation 	Field-Assembled	ASTM E283 ASTM E330 ASTM E331 ICC-ESR-1015	Cavity Wall (rainscreen)	Standard (½") and Variable Width (up to 12") Joints	15 Business Days

FEATURES & BENEFITS

- Performance Testing for Panel and System (including NFPA 285)
- Fire Resistant
- Impact Resistant
- Water Resistant
- Curvable
- Easliy Cut-To-Size in the Field
- Thermal Stability
- Low Maintenance
- Quick Lead Time

STANDARD SIZES

- **Width:** 48" or 60"
- **Length:** 96", 120", or 144"

WARRANTY

- **Panel Warranty:** 10 Years
- **Anodized Finish:** 20 Years
- **Kynar 500 Finish:** 30 Years (coil-coated)

INSULATED METAL WALL PANELS



FEATURES & BENEFITS

- **Joint:** Offset double tongue-and-groove
- **Core:** Continuously poured-in-place polyisocyanurate insulating foam
- **R-Value:** R-8 per inch of thickness (nominal)

PAC-CLAD insulated metal panels offer unsurpassed thermal efficiency for commercial and industrial buildings, and include a unique joint design to help ensure a high-performance vapor seal. Exterior aesthetics range from the look of tilt-up concrete to a sleek architectural design, and include cost-effective options.

COLORS: The PAC-CLAD colors on pages 4-7 do not apply to Insulated Metal Panels. Consult Petersen rep for color options.



DESIGN-LOK

- **Coverage width:** 42-inch
- **Thickness:** 2, 2.5, 3, 4-inch
- **Length:** 8'-0" to 40'-0"
- **Exterior gauges:** 26, 24
- **Interior gauge:** 26



MESA-LOK™

- **Coverage width:** 42-inch
- **Thickness:** 2, 2.5, 3, 4, 5, 6-inch
- **Length:** 8'-0" to 53'-0"
- **Exterior gauges:** 26, 24, 22
- **Interior gauge:** 26



MESA-LOK HSE™

- **Coverage width:** 42-inch
- **Thickness:** 2, 2.5, 3, 4, 5, 6-inch
- **Length:** 8'-0" to 53'-0"
- **Exterior gauges:** 26, 24
- **Interior gauge:** 26




SHADOW-LOK

- **Coverage width:** 42-inch
- **Thickness:** 2, 2.5, 3, 4, 5, 6-inch
- **Length:** 8'-0" to 53'-0"
- **Exterior gauges:** 26, 24, 22
- **Interior gauge:** 26




CORR-LOK

- **Coverage width:** 42-inch
- **Thickness:** 2, 2.5, 3, 4-inch
- **Length:** 8'-0" to 40'-0"
- **Exterior gauges:** 24, 22
- **Interior gauge:** 26



MAX-LOK

- **Coverage width:** 45-inch
- **Thickness:** 3, 4, 5, 6-inch
- **Length:** 8'-0" to 53'-0"
- **Exterior gauges:** 26
- **Interior gauge:** 26



RIDGE-LOK™

- **Coverage Width:** 42-inch
- **Thickness:** 2.5, 3, 4, 5, 6-inch
- **Length:** 12'-0" to 53'-0"
- **Exterior Gauge:** 26, 24, 22
- **Interior Gauge:** 26
- **Core:** Continuously poured-in-place polyisocyanurate insulating foam
- **R-Value:** R-8 per inch of thickness (nominal)
- **Minimum Slope:** ½:12R-Value
- **U.S. Patent:** 9,206,606 B2

INSULATED METAL ROOF PANEL


Ridge-Lok is the IMP industry's premier insulated standing-seam roof panel. The patented tee-seam allows for sliding the panels together rather than lifting and/or rolling the panels into place. The interior tongue-and-groove joint, coupled with a factory-caulked batten, helps provide a double layer of weather-tight protection.



PERFORATED METAL


Petersen offers perforation of select PAC-CLAD metal wall panels and flat sheet. Perforated panels and metal can provide a contrasting look with any non-perforated metal to create visual interest on any project. Architects can specify perforated aluminum and copper to diffuse light, air or sound, or simply for architectural flair. Typical applications include equipment screens, partitions, sign panels, parking decks, guards, interior acoustical applications and enclosures of any kind.

Perforation is available in a nearly endless combination of hole sizes, spacing and open space percentages to complement virtually any architectural design or need. Perforation options will vary by panel profile and metal thickness; consult factory for details.



Ballet Memphis, Memphis, TN
Installing contractor: Ralph Jones Sheet Metal
Architect: archimania
General contractor: Grinder, Taber & Grinder
Photo: Courtesy of archimania
Profiles: Snap-Clad, Corrugated solid and perforated
Colors: Zinc, natural copper material

THE MOST POPULAR EXAMPLES ARE SHOWN BELOW. ADDITIONAL OPTIONS ARE AVAILABLE.



a b c d e f g

For availability details, match the letters beneath each image with the letters in the chart below.


PATTERN SPECS				AVAILABLE ROLL-FORMED PANELS								SHEET
	DIAMETER	CENTERS (staggered)	OPEN AREA	FLUSH/ REVEAL	HWP	HIGHLINE	BOX RIB	7/8 CORRUGATED	7.2 PANEL	R-36	M-36	
a	1/8" Round	0.324"	13.5%	**	✔	✔	✔	✔	✔	✔	✔	✔
b	1/4" Round	1/2"	23%	**	✔	✔	✔	✔	✔	✔	✔	✔
c	1/8" Round	1/4"	23%	**	✔	✔	✔	✔	✔	✔	✔	✔
d	1/8" Round	7/32"	30%	**	✔	✔	✔	✔	✔	✔	✔	✔
e	3/16" Round	5/16"	33%	**	✔	✔	✔	✔	✔	✔	✔	✔
f	1/4" Round	3/8"	40%	**	✔	✔	✔	✔	✔	✔	✔	✔
g	3/8" Round	9/16"	40%	**	✔	✔	✔	✔	✔	✔	✔	✔

✔ Available in .032, .040 and .050 roll-formed products | ** Available in .032 and .040 roll-formed products


Consult local factory for additional pattern options not shown on the above chart.

Notes: ▸ Extra charges are applied for perforation ▸ Steel will not be perforated ▸ Limitations might apply for certain perforation specs; check with Petersen facility for details and options.

PAC-CLAD® WALL AND ROOF PANEL APPLICATIONS



Wildcat Stadium and Innovative Learning Destination, Godley, TX
Installing contractor: Ramon Franklin LLC
Architect: Huckabee
Distributor: ABC Supply
General contractor: Satterfield & Pontikes
Photo: alanblakely.com
Profiles: Highline B2, HWP Wall and Soffit
Colors: Cityscape, Custom Purple



Ballet Memphis, Memphis, TN
Installing Contractor: Ralph Jones Sheet Metal
Architect: archimania
General contractor: Grinder, Taber & Grinder
Photo: Courtesy of archimania
Profiles: Snap-Clad, Corrugated solid and perforated
Colors: Zinc, natural copper material

PAC-CLAD® WALL AND ROOF PANEL APPLICATIONS




Huntsville Transit Center, Huntsville, AL
Installing contractor: Metal Roofing Solutions
Architect: Fuqua & Partners Architects
Distributor: Roofers Mart Southeast
General contractor: Consolidated Construction Company
Photo: hortonphotoinc.com
Profile: Snap-Clad w/striations
Color: Bone White



VyStar Parking Garage on Forsyth, Jacksonville, FL
Installing contractor: Miller Clapperton
Architect: Dasher Hurst Architects
General contractor: Danis
Owner: VyStar Credit Union
Photo: hortonphotoinc.com
Profiles: 7.2 perforated, HWP w/clip
Colors: Silversmith, Bone White, Weathered Zinc, Custom Luxe Blue



Pigeon Creek Welcome Center, Pleasant Lake, IN
Installing contractor: Millwood Roofing & Construction
Architect: Fosse & Associates Architects
General contractor: Crosby Construction
Owner: Indiana Department of Transportation
Photo: hortonphotoinc.com
Profile: Tite-Loc
Color: Silver



Glacier Bank Park, Kalispell, MT
Installing contractor: Peach State Roofing
Architect: A&E Design
Distributor: Horner & Associates
General contractor: Swank Enterprises
Owner: Ridge Run Operators
Photo: alanblakely.com
Profiles: 7/8 Corrugated, 1/2 Corrugated, Shop-Fabricated Edge Metals
Colors: Weathered Steel, Onyx

SNAP-CLAD PANELS

Snap-Clad panels feature architectural aesthetics as well as structural performance. Snap-Clad panels, produced in continuous lengths, are leveled to provide superior flatness and feature an optional factory-applied sealant bead for improved weather resistance. Maximum panel length varies by facility and minimum panel length is 4'. Consult factory for longer lengths.

Snap-Clad panels feature a 1-¾" leg height and a continuous interlock for improved structural performance and wind resistance. A concealed-fastener clip system allows for thermal expansion/contraction while providing extraordinary hold-down strength. Two clips are available: a standard clip for most mansard and fascia applications, and a high-performance clip for roofing applications and UL 90-rated assemblies.

TRIM

All flashing and trim shall be fabricated by manufacturer or qualified fabricator. Flashing shall be PAC-CLAD aluminum (.032 - .063 gauge as specified) or PAC-CLAD steel (24 gauge or 22 gauge as specified). A 35-year non-prorated finish warranty can be supplied covering finish performance. Minimum bending radius is 2T; consult rep for details. Vinyl masking is recommended on all fabrication applications where extra handling is expected. NOTE: The strippable film must be removed immediately after installation.

INSTALLATION

Snap-Clad panels are intended for use in roofing, mansard and fascia applications. Substrates may include ⅝" (min.) plywood, nailboard insulation or equal with an underlayment of ice and water shield applied horizontally from eave to ridge. Other substrates may include metal decking or rigid insulation in conjunction with bearing plates. A minimum 2:12 pitch is recommended in most applications. Contact Petersen for assistance with details on projects requiring lower slopes. For coastal applications, aluminum panels along with stainless steel clips must be used for warranty. Consult a local architect/engineer for compliance with local codes and conditions.

OIL CANNING

Jobsite factors such as temperature variation, unlevel substrate and/or improper installation may promote oil canning. Oil canning does not affect panel finish or structural integrity and therefore is not cause for rejection.

PRODUCT FEATURES

- Architectural/structural panel
- Factory-applied sealant available
- Continuous interlock
- Labor-saving one-piece design
- Pencil ribs upon request
- Striations upon request
- 35-year non-prorated finish warranty
- Maximum factory-produced panel length varies by facility. Consult rep for details.
- Weathertightness warranty available

MATERIAL

- 24 gauge steel
- 22 gauge steel
- .032 aluminum
- .040 aluminum
- Panels available in Galvalume Plus

UL CLASSIFICATION

- UL-580 Class 90 wind uplift
- UL-1897 wind uplift
- UL-790 Class A fire rated
- UL-263 fire resistance rated
- UL-2218 impact resistance rated
- UL-90 rated aluminum panel up to 16" O.C.
- UL-90 rated steel panel up to 18" O.C.

ASTM TESTS

- ASTM E1592 tested
- ASTM E283/1680 tested
- ASTM E331/1646 tested

FLORIDA BUILDING & MIAMI-DADE PRODUCT APPROVALS

Please refer to pac-clad.com or your local factory for specific product approval numbers for Snap-Clad.



Destin Commons, Destin, FL
Installing contractor: Roof Specialties
Architect: JPRA Architects
Distributor: CRS – Commercial Roofing Specialties
Photo: hortonphotoinc.com
Profile: Snap-Clad
Colors: Arcadia Green, Slate Gray, Terra Cotta



UL 90 ICC ES


SNAP-CLAD

MATERIALS

.032 aluminum	24 gauge steel
.040 aluminum	22 gauge steel

SPECS

10", 12", 16" or 18" O.C.	1-3/4" High



NOTE: Oil canning is not a cause for rejection.



Las Vegas Ballpark, Las Vegas
Contractor: Southwest Specialty Contractors
Architect: HOK
General contractors: Penta Building Group; AECOM Hunt
Owner: Howard Hughes Corp.
Photo: Alan Blakely
Profile: Snap-Clad
Color: Custom Chocolate Chip

TITE-LOC PANELS



Sevier County Utility District multipurpose facility, Sevierville, TN
Installing contractor: Baird and Wilson Sheetmetal
Architect: BarberMcMurry Architects
Distributor: Baird and Wilson Sheetmetal
General contractor: Denark Construction
Owner: Sevier County Utility District
Photo: hortonphotoinc.com
Profiles: Snap-Clad, Tite-Loc, Flush panel
Colors: Musket Gray, Berkshire Blue

Tite-Loc panels combine structural performance with architectural aesthetics. Tite-Loc panels are leveled for flatness. A factory-applied sealant bead can be applied for additional weather resistance. Maximum panel length is 64′ and minimum length is 4′. Consult factory for longer lengths.

Tite-Loc panels feature a 2″ leg height that requires mechanical field seaming after installation. Panels have a concealed-fastener floating clip system designed to allow for thermal expansion/contraction.

TRIM

All flashing and trim shall be fabricated by manufacturer or qualified fabricator. Flashing shall be PAC-CLAD aluminum or steel. A 35-year non-prorated finish warranty can be supplied covering finish performance. Minimum bending radius is 2T; consult rep for details. Vinyl masking is recommended on all fabrication applications where extra handling is expected. NOTE: The vinyl film must be removed immediately after installation.

INSTALLATION

Tite-Loc panels are intended as architectural or structural roofing. Substrates may be ⅝″ (min.) plywood, nailboard insulation or equal with an underlayment of ice and water shield applied horizontally from eave to ridge. Other substrates can be metal decking, purlins or rigid insulation in conjunction with bearing plates. A minimum ½:12 pitch is required.

For coastal applications, aluminum panels with stainless steel clips must be used for finish warranty. Consult a local architect/engineer for compliance with local codes.

TITE-LOC/TITE-LOC PLUS PANELS

Tite-Loc and Tite-Loc Plus panels are factory-formed to length and field-seamed to a 90° lock (Tite-Loc) or a 180° lock (Tite-Loc Plus). The panels have been designed for application over a wide variety of substrates on roof slopes as low as ½:12 pitch. Available in 12″, 16″ and 18″ widths, Tite-Loc and Tite-Loc Plus panels can be produced in 22 and 24 gauge steel or .032 and .040 aluminum.

SEAMING

Tite-Loc and Tite-Loc Plus panels require the use of mechanical seamers. When seaming panels on slopes greater than 6:12, caution must be exercised to prevent seamer slippage and resulting finish scratches that may void the warranty. Seamers are available along with hand crimpers and other tools through D.I. Roof Seamers, which is the only supplier of this equipment approved by Petersen. For details and rental information visit pac-clad.diroofseamers.com.

CURVED APPLICATIONS

The Tite-Loc panels can be curved to a minimum radius of 20′. Tite-Loc curving can be done in the field or at the factory depending on the radius and length of the panel. Tite-Loc Plus panels cannot be curved. For more about Petersen's curving capabilities, contact your local Petersen factory.

OIL CANNING

Jobsite factors such as temperature variation, unlevel substrate and/or improper installation may promote oil canning. Oil canning does not affect panel finish or structural integrity and therefore is not cause for rejection.




TITE-LOC


MATERIALS


.032 aluminum*
.040 aluminum*
24 gauge steel*
22 gauge steel*


SPECS


12", 16" or 18" O.C.
2" High












TITE-LOC PLUS


MATERIALS


.032 aluminum*
.040 aluminum*
24 gauge steel*
22 gauge steel*


SPECS

12", 16" or 18" O.C.
2" High









NOTE: Oil canning is not a cause for rejection.

Not all panel conditions are available in each Petersen branch; additional freight charges might apply if specific panel condition is required. Tite-Loc and Tite-Loc Plus panels are supplied "smooth" as standard. Customer must advise if additional panel conditions are required.



Cape Canaveral Volunteer Fire Station,
Cape Canaveral, FL
Contractor: Quality Metals
Architect: BRPH
General contractor: W&J Construction
Photo: hortonphotoinc.com
Profile: Tite-Loc Plus
Color: Arcadia Green (retired color)

PRODUCT FEATURES

- Pencil ribs and striations are only available by request
- 35-year non-prorated finish warranty
- Maximum factory-produced panel length varies by facility. Consult rep for details.
- Weathertightness warranty available

MATERIAL

- 24 gauge steel
- .032 aluminum
- 22 gauge steel
- .040 aluminum
- Galvalume Plus available

UL CLASSIFICATION

- UL-580 Class 90 rated up to 18" O.C.
- UL-1897 wind uplift
- UL-790 Class A fire rated
- UL-263 fire resistance rated
- UL-2218 impact resistance rated

TESTS (TITE-LOC PLUS ONLY)

- 24 Gauge Steel SSTD Missile Impact Tested - Passed
- .032 Aluminum SSTD Missile Impact Tested - Passed
- ICC 500

ASTM TESTS

- ASTM E1592 tested
- ASTM E331/1646 tested
- ASTM E283/1680 tested
- ASTM E2140 (Tite-Loc Plus only)

FLORIDA BUILDING & MIAMI-DADE PRODUCT APPROVALS

Please refer to pac-clad.com or your local factory for specific product approval numbers for Tite-Loc Plus.

*24 gauge and 22 gauge steel and .032 and .040 aluminum panels are UL-90 classified over solid substrate. See roof deck construction in Underwriter Laboratories roofing materials and systems directory.
**24 gauge and 22 gauge Tite-Loc Plus panels are FM Approved in 12" and 16" widths over 16 gauge open purlins only.

PAC-150 PANELS



Raleigh Iron Works, Raleigh, NC
Installing contractor: Hamlin Companies
Architect: LS3P
Distributor: Beacon Building Products (M-36 only)
General contractor: Brasfield & Gorrie
Photo: hortonphotoinc.com
Profiles: Snap-Clad w/striations, Tite-Loc Plus w/striations, M-36
Color: Zinc (retired color)

PAC-150 standing seam metal roofing panels combine semi-structural metal panel performance with architectural roofing panel aesthetics. Maximum panel length is limited when factory or shop-formed but virtually unlimited when field-formed; minimum panel length is approximately 4'.

PAC-150 roofing panels feature a 1.5" leg height which requires mechanical field seaming to either 90° or 180°. Panels have a concealed-fastener clip designed to allow for maximum design flexibility.

This panel combines an attractive thin-rib profile with superior structural performance. PAC-150 panels are designed for application over a variety of substrates in slopes as low as 1:12. PAC-150 roofing panels are available in a variety of widths from 12" to 20".

OIL CANNING

Jobsite factors such as temperature variation, unlevel substrate and/or improper installation may promote oil canning. Oil canning does not affect panel finish or structural integrity and therefore is not cause for rejection.

REGIONAL AVAILABILITY


PAC-150 is produced only in Petersen's Georgia, Maryland and Arizona facilities; additional freight charges might apply.

CURVED APPLICATIONS

The PAC-150 panels can be curved to a minimum radius of 20'. Curving can be done in the field or at the factory depending on the radius and length of the panel. For details about curving capabilities, please contact the Acworth, Ga., or Annapolis Junction, Md., factories.

SEAMERS

PAC-150 panels require the use of mechanical seamers. When seaming panels on slopes greater than 6:12, caution must be exercised to prevent seamer slippage and resulting finish scratches that may void the warranty. Seamers are available along with hand crimpers and other tools through D.I. Roof Seamers, which is the only supplier of this equipment approved by Petersen. For details and rental information visit pac-clad.diroofseamers.com.




PAC-150 90˚ SEAM

MATERIALS


.032 aluminum 24 gauge steel

SPECS

12", 16", 18" or 20" O.C. 1-1/2" High



NOTE: Oil canning is not a cause for rejection.




PAC-150 180˚ SEAM

MATERIALS

.032 aluminum 24 gauge steel

SPECS

12", 16", 18" or 20" O.C. 1-1/2" High



PRODUCT FEATURES

- 35-year non-prorated finish warranty
- Weathertightness warranty available
- Available in four pan variations; smooth, striated, pencil rib or flat rib. Check locally for panel condition availability
- Maximum panel length of 64' when factory or shop-formed but virtually unlimited when field-formed
- Mechanically seamed in the field to 90° or 180°
- NOTE: Seamers for PAC-150 are available from pac-clad. diroofseamers.com

MATERIAL

- 24 gauge steel
- .032 aluminum
- Galvalume Plus available

UL CLASSIFICATION

- UL-580
- UL-1897
- TAS-125

FLORIDA BUILDING PRODUCT APPROVALS

Contact the Acworth, Georgia facility for PAC-150 product approvals.

Photo below: Theodore Roosevelt Visitor Center, Onward, MS
Contractor: Central Roofing
Architect: John S. Odom
Distributor: MS Roofing Supply
Owner: U.S. Fish and Wildlife Service
Photo: hortonphotoinc.com
Profile: PAC-150
Color: Weathered Steel



PAC T-250 PANELS



Prince Frederick Fire Department #2, Prince Frederick, MD
Installing contractor: Orndorff & Spaid
Architect: Bignell Watkins Hasser Architects
General contractor: S E Davis Construction
Owner: Prince Frederick Volunteer Fire Department
Photo: hortonphotoinc.com
Profiles: Tite-Loc Plus, Reveal wall and soffit panels
Color: Dark Bronze

PAC T-250 panels are factory-formed or field formed to length and field-seamed. The panels have been designed for application over a variety of substrates on roof slopes as low as ½ : 12. PAC T-250 panels combines structural panel performance with architectural panel aesthetics. PAC T-250 panels feature a 2.5" nominal finished panel height from the deck with seam cap that requires mechanical field seaming after installation. T-250 panels have a continuous and/or intermittent concealed-fastener clip system to allow for thermal expansion/contraction. Adhesive beads are factory-applied to seam cover.

TRIM

All flashing and trim shall be fabricated by manufacturer or qualified fabricator. Flashing shall be PAC-CLAD aluminum or steel. Minimum bending radius is 2T. Vinyl film is recommended on all fabrication applications where extra handling is expected. NOTE: The vinyl film must be removed immediately after installation.

OIL CANNING

Jobsite factors such as temperature variation, unlevel substrate and/or improper installation may promote oil canning. Oil canning does not affect panel finish or structural integrity and therefore is not cause for rejection.

INSTALLATION

PAC T-250 panels are intended for use in architectural and structural roofing. Substrates may include 5/8" min. plywood, nailboard insulation or equal with an underlayment of ice and water shield applied horizontally from eave to ridge. Other substrates may include metal decking, purlins or rigid insulation in conjunction with bearing plates. Maximum seam cap length is 25'. Contact Petersen for further assistance with project details. For coastal applications, aluminum panels along with stainless steel clips must be used for finish warranty. Consult a local architect/engineer for compliance with local codes and conditions. The panel is bi-directional, which allows installers to position the first panel in the center of a roof and install simultaneously in both directions.

SEAMING

PAC T-250 panels require the use of mechanical seamers, which are available along with hand crimpers and other tools through D.I. Roof Seamers, which is the only supplier of this equipment approved by Petersen. For details and rental information visit pac-clad.diroofseamers.com.

REGIONAL AVAILABILITY

PAC T-250 is produced only in Petersen's Illinois and Texas facilities; additional freight charges might apply.

PRODUCT FEATURES

- Smooth panels are standard
- Maximum factory-produced panel length varies by facility. Consult rep for details.
- Architectural/structural panel
- Factory-applied sealant in seam cover
- 35-year non-prorated finish warranty
- Field forming panels are available for long length requirements
- Can be tapered and radiused; consult factory for limitations
- Weathertightness warranty available
- Continuous and/or intermittent clips
- Not available in all locations. Consult PAC rep for availability.

MATERIAL

- 24 gauge steel
- 22 gauge steel
- Galvalume Plus available
- .032 aluminum
- .040 aluminum

TESTING

- ASTM 283 & 331 tested
- ASTM 1680 & 1646 tested
- ASTM E1592 tested
- ASTM E2140 tested
- FM 4474
- UL-580
- UL-897




PAC T-250


MATERIALS


.032 aluminum
.040 aluminum
24 gauge steel
22 gauge steel

SPECS

16", or 18" O.C.
2-5/8" nominal high









* Offered only in Illinois facility

NOTE: Oil canning is not a cause for rejection.



Georgia Sheriffs' Youth Homes Foundation, Madison, GA
Installing contractor: Infinity Metal Systems
Architect: Precision Planning Inc.
General contractor: Dublin Construction Co.
Photo: hortonphotoinc.com
Profiles: Tite-Loc Plus w/striations
Color: Aged Bronze

SNAP-ON PANELS


Bells Mill Elementary School, Potomac, MD
Installing contractor: CitiRoof Corporation
Architect: Walton, Madden, Cooper, Robinson, Poness Inc
General contractor: Oak Contracting
Owner: Montgomery County Public Schools
Photo: Shayne Hensley
Profile: Snap-On Batten (retired product)
Colors: Hemlock Green, Colonial Red, Sandstone, Slate Gray

Snap-On panels are ideal for use in roofing, mansard and fascia applications. Snap-On panels are designed to be installed over a waterproofed solid substrate and a minimum 3:12 roof pitch. Snap-On panels are factory roll-formed in continuous lengths. Maximum panel length is 35′ and minimum panel length is 4′. Consult factory for nonstandard lengths.

The simplicity of the pan design combined with leveling provides superior flatness and allows for greater workability on site.

TRIM

All flashing and trim shall be fabricated by manufacturer or qualified fabricator. Flashing shall be PAC-CLAD aluminum (.032 - .063 gauge as specified) or PAC-CLAD steel (24 gauge or 22 gauge as specified). A 35-year non-prorated finish warranty can be supplied covering finish performance. Minimum bending radius is 2T; consult rep for details. Vinyl masking is recommended on all fabrication applications where extra handling is expected. NOTE: The strippable film must be removed immediately after installation.

INSTALLATION

Snap-On panels shall be installed over solid decking (⅝" plywood, nailboard insulation or equal) with an underlayment applied horizontally from eave to ridge. Panels shall be fastened using Petersen nonpenetrating clips, fastening on 18" centers (max.). Minimum slope at 3:12 pitch. Consult a local architect or engineer for requirements of local codes and conditions.

CURVED PANELS

The 1" Snap-On standing seam panel can be curved to a concave or convex radius, with a minimum radius of 9′. This panel is ideal for barrel vaults and entrance ways. Curved panels must be installed over a waterproofed solid substrate.

OIL CANNING

Jobsite factors such as temperature variation, unlevel substrate and/or improper installation may promote oil canning. Oil canning does not affect panel finish or structural integrity and therefore is not cause for rejection.

PRODUCT FEATURES

- Ideal for transition roofs
- Pencil ribs available
- 35-year non-prorated finish warranty
- Panel lengths up to 35′

MATERIAL

- 24 gauge steel
- .032 aluminum
- Galvalume Plus available

UL CLASSIFICATION

- UL-1897 wind uplift
- UL-790 Class A fire rated
- UL-263 fire resistance rated

ASTM TESTS


- ASTM E283/1680 tested
- ASTM E331/1646 tested

FLORIDA BUILDING PRODUCT APPROVALS

Please refer to pac-clad.com or your local factory for specific product approval numbers for Snap-On Panels.



Limetree Beach Resort, St. Thomas, USVI
Installing contractor: Central Roofing
Architect: Silverberg Associates
General contractor: J. Benton Construction
Owner: Captain's Command at Bluebeard's Beach Club Owners' Association
Photo: Brian Adams
Profile: Tite-Loc Plus
Color: Interstate Blue



UL 90

SNAP-ON STANDING SEAM

MATERIALS


.032 aluminum

24 gauge steel*

SPECS


12", 16", 18" or 20" O.C.**

1" High



NOTE: Oil canning is not a cause for rejection.

*12" and 18" 24 gauge steel Snap-On Standing Seam panels are UL-90 Classified over solid substrate. See roof deck construction in Underwriter Laboratories roofing materials and systems directory. A complete specification is available at pac-clad.com.




Sandra Stetson Aquatic Center, DeLand, FL
Installing contractor: Quality Metals Inc.
Architect: Preston T. Phillips Architect
General contractor: Charles Perry Partners Inc.
Photo: hortonphotoinc.com
Profile: PAC-150
Color: Custom Stetson Green

**** Panel width varies by factory. Consult PAC rep for details.**

PAC-CLAD® WALL AND ROOF PANEL APPLICATIONS



Martha Cooper Library Expansion, Tucson, AZ
Installing contractor: Starkweather Roofing
Architect: Line and Space, LLC
Distributor: Roofers Mart Southeast
General contractor: Kappcon Inc.
Photo: alanblakely.com
Profile: Reveal wall panel
Color: Musket Gray



Micky Elliott College of Fine Arts, Nacogdoches, TX
Installing contractor: Reneau Roofing and Sheet Metal
Architect: Kirksey Architecture
Distributor: Roofers Mart Southeast, Steinberg Hart
Photo: alanblakely.com
Profiles: Precision Series Tiles, Highline B1, Highline S1
Color: Light Interference Color (LIC), Champagne




Parc Haven at Symphony Park, Las Vegas, NV
Installing contractor: TLC Roof Services
Architect: Callison RTKL
Distributor: ABC Supply, Las Vegas, NV
General contractor: Martin Harris
Photo: alanblakely.com
Profiles: Highline B2, Flush, 7.2, Snap-Clad
Colors: Musket Gray, Berkshire Blue, Patina Green



Integrated Architecture, Grand Rapids, MI
Installing contractor: Action Roofing & Sheet Metal
Architect: Integrated Architecture
General contractor: FCC Construction
Distributor: Oakland Metal Sales
Photo: jmaconochie.com
Profile: HWP
Color: Weathered Zinc

SOFFIT PANELS



Palmer Bank, Taylorville, IL
Contractor: E.L. Pruitt Company
Architect: The Redmond Company
General contractor: The Redmond Company
Photo: Scott Bell
Profiles: Snap-Clad, PAC-850 Vented Soffit, Flush panel
Colors: Charcoal and Slate Gray

Petersen offers superior design versatility for soffit applications by providing the PAC-750/850 Soffit panels, as well as the Flush panel in a variety of gauges and widths. Both pre-formed profiles are effective solutions in soffit projects, and with the aluminum substrate can be ventilated for increased airflow capacity.

PAC-750 SOFFIT PANELS

Petersen offers a pre-formed soffit panel suitable for both commercial and residential use. Panels are 12" wide with a "vee" groove every 6" center-to-center and furnished in continuous lengths up to 25'. Minimum panel length varies by location. Consult rep.

PAC-850 SOFFIT PANELS

PAC-850 Soffit panels utilize an innovative hook-and-grab interlock. Panels are 12" wide with a "vee" groove every 6" center-to-center and furnished in continuous lengths of up to 25'. Minimum panel length varies by location. Consult rep.

SOFFIT VENTING

The PAC-750 and PAC-850 Soffit panels can be lanced to allow for airflow and under-eave ventilation in full or half vent.. See illustrations on page 41 for examples and limitations.

SOFFIT "J" CHANNEL

Petersen can provide soffit "J" Channel as trim in lengths up to 12' in matching colors.

FLUSH PANELS

The Flush panel and Reveal panel may be specified for use as soffit panels. Maximum panel length is 25' and minimum panel length is 4'. Pencil ribs can be added to the Flush panel for increased strength and aesthetics. Pencil ribs are recommended for longer panel lengths. One or two ribs are available at no additional cost. See drawings on page 15.

FLUSH AND REVEAL VENTING

The Flush and Reveal panels only in .032 aluminum are available ventilated. Consult the local factory for venting options.

OIL CANNING

Jobsite factors such as temperature variation, unlevel substrate and/or improper installation may promote oil canning. Oil canning does not affect panel finish or structural integrity and therefore is not cause for rejection.

PRODUCT FEATURES

- Four profiles available
- Perforation available for ventilation on aluminum only
- Roll-formed to exact lengths
- Matching "J" trim available
- 35-year non-prorated finish warranty

MATERIAL

- 24 gauge steel (Flush/Reveal soffit only)
- 22 gauge steel (Flush/Reveal soffit only)
- .032 aluminum
- .040 aluminum
- Galvalume Plus available (Flush and Reveal soffit only)

ASTM TESTS

- ASTM E330 Tested: Flush panel (12" only) and PAC-850
- ASTM 1592
- ASTM E331
- ASTM E283
- AAMA 501.1-05

FLORIDA BUILDING PRODUCT APPROVALS

Please refer to pac-clad.com or your local factory for specific product approval numbers for soffit panels.

OPEN AIR PERCENTAGES (750/850/FLUSH)

(these percentages are nominal and may vary per profile)

- Half vented (750/850) - 6%
- Full vented (750/850) - 12%
- Wide vent (Flush/Reveal) - 12%
- Narrow vent (Flush/Reveal) - 6%

SOLID



HALF VENT




FULL VENT




PAC-750


MATERIALS	SPECS
.032 aluminum	12″ O.C.



SOLID



HALF VENT




FULL VENT



PAC-850


MATERIALS	SPECS
.032 aluminum	12″ O.C.






Towner County Medical Center, Cando, ND
Installing contractor: MG McGrath
Architect: Infusion Architects
General contractor: Mortenson
Photo: alanblakely.com
Profiles: Flush wall panel, Flush soffit
Colors: Charcoal, Long Grain Cherry

REVEAL SOLID



FLUSH SOLID



SOFFIT FLUSH AND REVEAL


MATERIALS


.032 aluminum	24 gauge steel
.040 aluminum*	22 gauge steel*

*Limited color availability

SPECS

7″, 11″, or 12″ O.C. 1″ High






NOTE: Oil canning is not a cause for rejection. An oil canning agreement is required when ordering lengths over 8′-0″ (24 ga. steel or .032″ aluminum) and over 20′-0″ (22 ga. steel or .040″ aluminum).

VENTING OPTIONS	7″	11″	12″
FLUSH WIDE VENT		✔	✔
FLUSH NARROW VENT	✔	✔	✔

.032 aluminum only



PAC-SHIELD ROOFING INSULATION

Petersen's PAC-Shield polyiso roof and wall insulation products contain no HFCs, CFCs, or HCFCs and are made using recycled materials. Thermal efficiency and sustainability are two cornerstones of PAC-Shield panels, which can help reduce a building's carbon footprint with virtually no global warming potential and have zero ozone-depleting potential. LEED credits can be given by utilizing PAC-Shield products in the areas of optimizing energy performance, thermal comfort, building life-cycle impact reduction, and more.

PAC-Shield CV is a vented option for steep-slope roofing applications of 3:12 slope or greater and is appropriate for standing seam metal, shingles, slate (natural and synthetic) and tile.




PAC-SHIELD

DIMENSIONS
4′ x 4′, 4′ x 8′

R-VALUE
5.7 – 26.8

THICKNESS
1″ – 4.5″

PSI
20 or 25




PAC-SHIELD COATED GLASS

DIMENSIONS
4′ x 4′, 4′ x 8′

R-VALUE
5.7 – 26.8

THICKNESS
1″ – 4.5″

PSI
20 or 25



PAC-SHIELD NAIL BASE


DIMENSIONS
48″ x 96″
47.5″ x 47.5″ (OSB)
47.5″ x 95.5″ (OSB)

R-VALUE
6.3 – 21.1

PSI
20 or 25

THICKNESS
1.6″ – 4.2″
1.5″ – 4.1″ (OSB)





PAC-SHIELD CV

DIMENSIONS
4′ x 8′

R-VALUE
5.7 – 20.5

THICKNESS
2.5″ – 5″


PSI
20

Photo Left:
Mowbray Volunteer Fire Station, Chattanooga, TN
Installing contractor: Davis Brothers Roofing
Architect: MBI Companies
Owner: Hamilton County Tennessee
Photo: hortonphotoinc.com
Profiles: Tite-Loc Plus, HWP, Flush panel
Color: Slate Gray, Matte Black Steel, Granite

PAC-SHIELD CI WALL INSULATION

Photo Right:
UTSA Guadalupe Hall, San Antonio, TX
Installing contractor: Corey Construction
Architect: Alamo Architects, Inc.
General contractor: The Whiting-Turner Contracting Company
Photo: alanblakely.com
Profiles: HWP, Flush panel
Colors: Almond, Slate Gray, Terra Cotta





PAC-SHIELD CI FOIL AND FOIL (CLASS A)

THICKNESS	R-VALUE
1″ – 4″	6.5 – 27.0 (Foil) 6.3 – 25.2 (Foil Class A)



PAC-SHIELD CI COATED GLASS AND COATED GLASS (CLASS A)

THICKNESS	R-VALUE
1″ – 4″	6 – 25



PAC-SHIELD CI PLY AND PLY (CLASS A)

THICKNESS	R-VALUE
1.6″ – 4.7″	6.8 – 26



PAC-SHIELD CI NAIL BASE

THICKNESS	R-VALUE
1.5″ – 4.5″ (OSB) 1.6″ – 4.6″ (ply)	6.6 – 25.6 (OSB) 6.8 – 25.8 (ply)

PAC-CLAD HT UNDERLAYMENT





PAC-CLAD HT from Petersen is a self-adhering, high-temperature roofing underlayment designed to provide premium waterproofing protection for a variety of roofing applications. PAC-CLAD HT underlayment offers protection against water and ice damming while withstanding extreme weather conditions.

The self-adhering qualities of PAC-CLAD HT reduces labor costs and installation times while providing increased protection compared to that of typical felt roofing underlayments. This strong, skid-resistant high-tensile-strength rubberized asphalt membrane is available in either black or white.

Note: Exposure to sunlight should not exceed 60 days for black and 180 days for white.

PRODUCT FEATURES

- Protects against water infiltration caused by ice dams and wind-driven rain
- Resists cracking, drying and rotting
- Resists temperatures up to 250°F without adhesive degradation
- Concealed waterproofing system will not detract from architectural aesthetics
- Exposed rubberized asphalt bead ensures watertightness of lap seams
- Seals around roofing fasteners
- Split-release film provides fast and easy installation

TESTING

- UL Classified
- ICC-ES ESR #2206
- 2009, 2012 and 2015 International Building Code
- Florida Building Code Approved Product #6785
- Meets ASTM D1970
- Miami-Dade County Product Control Approved
- ASTM E108/UL 790 Class A Fire Resistance
- 2016 California Green Building Standards, Title 24
- 2015, 2012 and 2008 ICC 700 National Green Building Standard

PRODUCT SPECIFICATIONS

PHYSICAL PROPERTIES		
Surface	Black/White Engineered Polyolefin Composite Film with Factory-applied Anti-skid Coating	
Membrane	Rubberized Asphalt	
PRODUCT CHARACTERISTIC	**UNITS**	**RESULTS**
Roll Length	feet	66
Roll Weight	lbs	55
Roll Size	sq ft	198
Roll Width	inches	36
PACKAGING INFORMATION		
Boxes (rolls) per pallet		25
TYPICAL PERFORMANCE PROPERTIES	**TEST METHOD**	**RESULTS**
Thickness	ASTM D1970	40 mils
Low Temperature Flexibility	ASTM D1970	-45°F
Adhesion to Plywood at 75°F	ASTM D1970	35 lbs/ft
Lap Seam Adhesion at 75°F	ASTM D1970	21 lbs/ft
Sealability Around Nail	ASTM D1970	Pass
Slip Resistance	ASTM D1970	Pass
Thermal Stability	ASTM D1970	Pass
Moisture Vapor Permeance	ASTM D1970	0.02 perms
Water Absorption	ASTM D1970	0.5%
Tensile Strength Machine Direction	ASTM D412	250 psi
Tensile Strength Transverse Direction	ASTM D412	1390 psi
Elongation at Break Machine Direction	ASTM D412	250%
Elongation at Break Transverse Direction	ASTM D412	170%

GUTTER AND DOWNSPOUT SYSTEMS

The design of the PAC-TITE gutters, downspouts and scuppers, improves water management performance while complementing a building's aesthetic qualities. Custom engineering, such as the heavy aluminum gutter strap design, also promotes ease of installation and helps the drainage systems withstand harsh environments. Petersen's PAC-TITE line is the only system that's Factory Mutual approved. It also features ANSI/SPRI GT-1 compliance.

GUTTERS

Superior roof drainage, easy installation, and attractive appearance make PAC-TITE prefabricated gutters and downspouts stand out from the crowd. Prefabricated PAC-TITE WR Gutters are specifically engineered and tested to meet the requirements of the ANSI/SPRI GT-1 Standard for Gutter Systems Used with Low-Slope Roofs. The design incorporates an extruded internal gutter hanger for strength and support. It also reduces the torque of the metal with expansion and contraction in temperature changes.

GUTTER PRODUCT FEATURES

- 30 Year, 160 MPH Wind Warranty
- ANSI/SPRI GT-1 Tested to Comply with International Building Code (WR only)
- FM Approved for Wind Uplift Protection
- Pre-Punched Holes and No External Brackets=Less Installation Time
- Prefabricated Miters and Accessories Eliminate Need for Field Fabrication
- Variety of Colors, Sizes and Materials



Prince Frederick Fire Department #2, Prince Frederick, MD (See page 34 for details)


DOWNSPOUTS

The PAC-TITE industrial downspout is available in a variety of standard sizes, or it can be fabricated to meet specific job requirements. The open-face design makes clearing out debris an easy task. Downspouts are manufactured with simple connection configurations and include three attachment straps per 12-foot section, which enables fast and easy installation.

SCUPPER, COLLECTION BOX


The PAC-TITE water drainage line includes a variety of custom-designed scuppers and collection boxes that meet performance requirements that architects and contractors want. Their unique design provides maximum protection against leaks, and is a decorative and functional means of water control.

PAC-TITE WR GUTTERS




Offset | Chamfer | Box

PAC-TITE LT GUTTERS




K-Style | Half Round

INDUSTRIAL DOWNSPOUTS




Closed | Open

LT DOWNSPOUTS



Corrugated | Round

SCUPPER, COLLECTION BOX



Thru-Wall Scupper | Thru-Wall Collection Box

COLORGARD® 2.0 SNOW RETENTION SYSTEM

Petersen is stocking the patented ColorGard 2.0 snow retention system, which is the only product available which will precisely match the color of any PAC-CLAD roof panel. ColorGard 2.0 achieves this by utilizing a strip of the actual roof material, which is then mounted directly into ColorGard 2.0 for a perfect match.



The design of ColorGard 2.0 simplifies the assembly process and significantly reduces installation time. Installers no longer are required to preassemble ColorGard 2.0 before getting on the roof — it is a true lay-and-play system for new construction and retrofit applications.

ColorGard 2.0 utilizes the patented S-5! clamp for its strength. The S-5! technology involves gripping the seam in such a way that there is no penetration to the panel material. S-5! utilizes round-point set screws for attachment which are specially made for the S-5! ColorGard 2.0 snow retention system. These systems eliminate minimum temperature installation requirements and messy adhesives to apply. ColorGard 2.0 can be installed at any temperature. For more information regarding ColorGard 2.0 please contact the local Petersen representative.

PAC-CLAD® FLASHING AND TRIM

Petersen offers custom-fabricated trim accessories that are formed in a gauge appropriate to the end-use application. Precisely matched color and finish quality is assured.

For projects in which installer-fabrication is preferred, flat sheet is available for immediate shipment.

A complete set of flashing details for each panel profile is available at pac-clad.com, and includes detailed drawings for many flashing conditions. These flashing details should be followed, especially for any projects requiring a weathertightness warranty. Assistance with difficult or unusual flashing conditions is available by contacting the local Petersen representative. In addition to standard details, Petersen can provide custom fabrication. Please contact Petersen for assistance with custom architectural elements.

Vinyl masking is recommended on all fabrication applications where extra handling is expected. NOTE: The strippable vinyl film must be removed immediately after installation.

Minimum bending radius is 2T; consult rep for details.




Florence Middle School, Florence, AL
Contractor: MG Roofing
Architect: Lambert Ezell Durham Architecture
Owner: Florence City Board of Education
Photo: hortonphotoinc.com
Profiles: Flush panels with ribs, Flush panels lanced, flat sheet
Color: Almond

FASCIA SYSTEMS

Designed with strength and performance in mind, PAC-TITE fascia products are tested to ANSI/SPRI/FM 4435/ES-1 standards for full compliance with the specification. Available in a multitude of steel and aluminum gauges and face heights, PAC-TITE fascia can meet the needs of any project condition. A lifetime 215 mph warranty is available for PAC-TITE fascia products. For additional design options, Petersen provides the PAC-LOC and the Snap Edge fascia systems.

- Superior, efficient design for ease of installation
- Extensively tested for reliable, long-term performance
- Welded corners and scuppers available (for aluminum products only)
- Wide variety of colors and finishes
- Pre-punched, slotted holes for precise fastener placement

PAC-TITE ANGULAR FASCIA



Fully Adhered/ Mechanically Attached Single-Ply (FA) | Built-Up/Modified (BUM)

PAC-TITE WT FASCIA



Fully Adhered/ Mechanically Attached Single-Ply (FA) | Built-Up/Modified (BUM)

PAC-TITE WT EXTENDED FASCIA



Fully Adhered/ Mechanically Attached Single-Ply (FA) | Built-Up/Modified (BUM)

PAC-TITE WT CANTED FASCIA



WT Extended Canted Fascia w/ Galvanized Waterdam | WT Canted Fascia w/ Galvanized Waterdam

PAC SNAP EDGE FASCIA



Fully Adhered/ Mechanically Attached Single-Ply (FA) | Built-Up/Modified (BUM)

PAC SNAP EDGE EXTENDED FASCIA



Fully Adhered/ Mechanically Attached Single-Ply (FA) | Built-Up/Modified (BUM)

PAC-LOC FASCIA



PAC-LOC FASCIA 2000 | PAC-LOC FASCIA 3000

COPING SYSTEMS

As a key protective element, roof edge and perimeter products are necessary to maintain the integrity of all flat roofing systems. Petersen offers a line of coping products to meet the most stringent engineering requirements as well as provide the ideal finishing touch for superior aesthetics.

- Superior, efficient design for ease of installation
- Extensively tested for reliable, long-term performance
- Welded corners and scuppers available (for aluminum products only)
- Wide variety of colors and finishes
- Pre-punched, slotted holes for precise fastener placement
- Non-penetrating design maintains watertightness integrity

PAC-TITE COPING



Tapered | Flat | Existing Slope with Nailer


PAC-TITE GOLD COPING



PAC-CONTINUOUS CLEAT COPING




COLUMN COVERS



1000 SERIES

- PAC-1000F (Flush Joint)
- PAC-1000C (Caulk Joint)
- PAC-1000R (Reveal Joint)



2000 SERIES


- PAC-2000F (Flush Joint)
- PAC-2000C (Caulk Joint)
- PAC-2000R (Reveal Joint)

PAC-1000 & 2000 SERIES


The design of the PAC-1000 and 2000 "F" Series Column Covers allows for a clean, precise installation, revealing a hairline joint. The column sections are assembled using a rivnut/keyhole system to provide a tight, inconspicuous vertical seam.

The PAC-1000 and 2000 "C" and "R" Series Column Covers are designed to leave a small open vertical reveal where the sections meet. Backer rod and caulk are applied to the vertical reveal joint to complete the installation of the "C" Series Column Cover. For the "R" Series Column, a metal channel filler is fabricated to fit into the vertical joint, and is set in sealant.


Projects may require column or section designs that are not shown here. Column Covers are available in 16 gauge stainless steel, and .090 and .125 aluminum, but check with rep to confirm. Finishes include custom colors, PAC-CLAD colors shown on pages 4-7, plus anodized options and composite material. Maximum length can vary. Petersen's fabrication capabilities offer flexibility and go far beyond what is displayed on this page. Please contact Petersen with fabrication needs.



FLUSH JOINT



CAULK JOINT



REVEAL JOINT

*NOTE: Consult factory if tighter radius for Reveal or Caulk Joint is required.

COIL AND FLAT SHEET



In addition to offering the industry's widest selection of 70% PVDF finishes in steel and aluminum, Petersen also provides mill finish sheet and coil in a variety of gauges and widths. Stock includes 5005-H34, as well as 3105 H24, in gauges .032 to .125 for all applications that require fabrication and post-finishing. With its state-of-the-art, cut-to-length and slitting equipment, Petersen can provide flat sheet and coil to exact specifications.

BENDING GUIDELINES

METAL BENDING GUIDELINES

Proper bending techniques must be followed when fabricating PAC-CLAD steel and aluminum. Failure to follow bending guidelines can result in product and/or paint failure. To remain in compliance with Petersen's finish warranty for PAC-CLAD metal, follow the guidelines outlined in this document.

BENDING TOLERANCES

The PAC-CLAD finish is engineered to be durable, but it can be stretched, cracked or exhibit compromised adhesion if bent beyond its tensile strength limits. Additionally, metal can crack, fracture or become weakened if bent improperly. The following tolerances apply when bending PAC-CLAD metal into 180-degree angles.

MATERIAL THICKNESS	BEND TYPE
.032" aluminum	2T
.040" aluminum	2T
.050" aluminum	2T
.063" aluminum	2T
22 gauge steel	2T
24 gauge steel	2T

FINISH WARRANTY COMPLIANCE

Reference to proper bending of Petersen's PAC-CLAD metal can be found in Part II, Section 3 of the 35-year finish warranty as follows:

"This warranty does not apply to failure of the coating in the following additional circumstances: forming where the bend is tighter than 2T, forming which involves severe reverse bending, or which subjects the coating to alternate compression and tension..."

TERMINOLOGY

Metal bends are given descriptions such as 0T, 1T, 2T, etc., where T refers to the thickness of metal. These designations are used to measure the inner radius of the bend applied to sheet metal in 90 and 180-degree bends.

QUESTIONS

Consult factory representative with questions or concerns.

TYPICAL BENDS

RECOMMENDED

90° 2T (TWO-T) BEND


The **outside** radius of the bend is equal to 2x the metal thickness.



2x the metal thickness

180° 2T (TWO-T) BEND

The **inside** radius of the bend is equal to 2x the metal thickness.



2x the metal thickness

VOIDS WARRANTY


90° BEND

The **inside** angle of the bend is 90 degrees. The thickness at the bend is less than the thickness of the material. Example: If using .040 aluminum the outside radius must be .080 or greater.



180° 0T (ZERO-T) BEND


The **inside** radius of the bend is zero. The legs of the bend are fully compressed together.



0x the metal thickness

180° 1T (ONE-T) BEND

The **inside** radius of the bend is equal to 1x the metal thickness.



1x the metal thickness

GENERAL CONSIDERATIONS

The following is a summary of conditions and considerations that Petersen considers important when specifying PAC-CLAD metal products. For project-specific information, please call 800-PAC-CLAD.

FINISHES

PAC-CLAD panels are available standard with a 70% PVDF finish. Please refer to the color information on pages 4 through 7 for guidance of color selection. Samples and photo-accurate color charts are available for your assistance.

CUSTOM COLORS

Custom colors are available for most applications of greater than 10,000 sq. ft. and may be applied to either aluminum or Galvalume steel. Contact Petersen for information concerning costs and availability.

INSTALLATION

Special care must be taken to ensure that panels are installed over a flat substrate. For roofing applications, panels typically are installed over ⅝" or ¾" plywood decking with ice and water shield horizontally overlayed from the eave to the ridge. It is recommended that clips be installed on 18" centers for all applications except Snap-Clad, PAC-150, PAC T-250, Tite-Loc Plus and Tite-Loc (consult specific UL Construction assemblies for clip spacing). Consult a local architect/engineer for requirements of local codes and conditions.

ACCESSORIES

Most applications require additional metalwork including fascia, storefront trim, copings, gravel stops, downspouts, etc. Such metalwork may be specified for fabrication by manufacturer or for fabrication from flat sheet as provided by manufacturer. Flashings properly fabricated from PAC-CLAD flat sheet are fully covered under Petersen's 35-year finish warranty.

PAC-CLAD flat sheet provides an exact color match to PAC-CLAD panels. PAC-CLAD flat sheets, coil and fabricated trim accessories are available with a strippable vinyl masking applied. This masking is recommended on all applications requiring extra handling. NOTE: This strippable vinyl film must be removed immediately after installation.

PANEL CONDITIONS/VARIATIONS

Pencil ribs and striations must be requested by the customer.

PANEL DIMENSIONS

All dimensions appearing in this catalog are nominal. Consult Petersen rep for more information.



LENGTHS

All panels are cut to custom lengths before roll-forming and are available in lengths up to 64'. See specific product pages for maximum panel lengths. Minimum length is 4'. Consult factory for longer lengths. Lengths are accurate to ¼". Custom cut-to-length service is available at no cost and helps to improve project economy.

PANEL WIDTHS

Most PAC-CLAD panels are available in non-standard on-center dimensions. Contact Petersen for product availability and cost. PAC-CLAD panel standard widths are nominal and could vary.

PITCH

Tite-Loc and PAC T-250 panels are designed for a roof pitch of ½:12 or greater. PAC-150 minimum pitch is 1:12. Snap-Clad panels have been designed to be installed on applications as low as 2:12 pitch. Snap-On panels have been designed for a minimum 3:12 pitch. Greater pitch may be required in snow country and in areas of extreme climate conditions.

Photo above:
Anne Carlsen Center, Jamestown, ND
Installing contractor: MG McGrath
Architect: JLG Architects
General contractor: Mortenson
Photo: alanblakely.com
Profiles: 7/8"Corrugated, 1/2" Corrugated
Colors: Bone White, Champagne
Custom Colors: Lemon Twist, Center Stage Green, Gulfstream, Purple

FIRE RATINGS

PAC-CLAD panels have been evaluated by Underwriters Laboratories for inclusion in a variety of fire-rated "P-Assemblies" and are classified in section CETW of the UL Fire Resistance Directory - Vol. 1. Several panel assemblies have been evaluated as Class A fire-rated. Contact Petersen for complete information on components and assemblies.

OIL CANNING

All Petersen material is prime-quality aluminum or Galvalume steel. All materials are specified for roll-forming applications. Panels are inspected in the plant for flatness before shipment. Jobsite conditions such as temperature variation, unlevel substrate and/or improper installation may promote oil canning. Oil canning does not affect the finish or structural integrity of the panel and is therefore not cause for rejection.

WARRANTY

A 35-year finish warranty is available covering cracking, peeling and color fade on all PAC-CLAD applications. PAC-CLAD is a 70% PVDF finish and therefore carries the highest-quality 35-year non-prorated finish warranty available. Finish warranty terms for Cardinal Red, Interstate Blue, Award Blue, Weathered Steel and all metallic finishes vary. Please refer to pac-clad.com for further details.

Petersen also offers a coastal finish warranty for projects located in the vicinity of the coast or within saltwater environments. Aluminum substrates, with stainless steel clips and fasteners, must be used to qualify for the coastal warranty.

For projects utilizing Snap-Clad, Tite-Loc, Tite-Loc Plus, PAC-150 and PAC T-250 factory-formed standing-seam panels, weathertightness warranties for terms up to 20 years are available. Projects must be approved for warranty by Petersen prior to ordering.

STORAGE


Clean, dry facilities for storage and protection of material should be provided at the job site. Store materials out of traffic areas to prevent dents, bending, abrasion, etc.

LIMITATIONS ON LIABILITY

Neither Petersen nor its customer shall be liable for special, indirect or consequential damages. The liability of Petersen in the event of the sale of its products shall be limited to replacement of any defective or nonconforming products or refund of the purchase price.

BENDING LIMITS

Bending limitations apply to PAC-CLAD metal. Bending beyond the approved 2T limit will void warranty. Refer to page 49, consult a Petersen rep for more information or visit pac-clad.com.



Texas A&M University Southside Rec Center, College Station, TX
Installing contractor: Auzmet Architectural
Architect: SmithGroup
General contractor: Manhattan Construction
Photo: alanblakely.com
Profiles: Box Rib 1, 2, 3, 4 (some perforated); Flush wall panel; Flush soffit
Color: Dark Bronze



Millennium High School, Goodyear, AZ
Installing contractor: Progressive Roofing
Architect: BWS Architects
General contractor: McCarthy
Owner: Agua Fria Unified School District
Photo: alanblakely.com
Profiles: Flush Panels
Colors: Weathered Zinc, Silver, Silversmith, Cityscape, Musket Gray, Custom Color Nike Purple



Altgeld Family Resource Center, Chicago
Installing contractor: Progressive Dynamics
Architect: KOO
Owner: Chicago Housing Authority
Photo: hortonphotoinc.com
Profiles: Snap-Clad, Corrugated, Snap-On, PAC-CLAD HT
Colors: Custom Dynamic Blue, Charcoal

- PRECISION SERIES WALL PANELS
- FLUSH AND REVEAL PANELS
- MODULAR AL PANEL SYSTEM
- BOARD & BATTEN WALL PANELS
- EXPOSED FASTENER PANELS
- COMPOSITE PANEL SYSTEMS
- INSULATED METAL PANELS
- PERFORATED METAL
- SNAP-CLAD PANELS
- TITE-LOC PANELS
- SNAP-ON PANELS
- PAC-150 PANELS
- PAC T-250 PANELS
- SOFFIT PANELS
- PAC-SHIELD INSULATION
- FASCIA SYSTEMS
- COPING SYSTEMS
- GUTTER AND DOWNSPOUT SYSTEMS
- PAC-SHIELD
- COIL AND FLAT SHEET

PAC-CLAD.COM | 800 PAC CLAD

PAC-CLAD® is a registered trademark of Petersen Aluminum Corporation
The PAC-CLAD finish is 70% polyvinylidene fluoride (PVDF). 1/26

SAP 614847

PAC-CLAD
PETERSEN